

PRODUCT

SKU/ColorNames :

XL-01 Biscotti	XL-06 Porcini
XL-02 Oat	XL-07 Truffle
XL-03 Sea Salt	XL-08 BonBon
XL-04 Oyster	XL-09 Caramel
XL-05 Maple	XL-10 Mocha

Construction :

- 6mm Rigid Core (Stone and Virgin DOTP Composite) (Single Extrusion Stone Polymer Composite)
- 1mm IXPE attached cushion (No VOCs)
- 8 unique planks per pattern, 16 with a flip

Wear Layer :

20mil with Quantum X[™] Technology Finish

Installation :

- Click, Valinge Locking System
- Float or Glue Down
- 100 LF before transition needed
- Matching Accessories: 3-in-1 Molding, Stair Tread, Flush Stair Nose
- Use Polyurethane for wet spaces. Pressure sensitive adhesive is acceptable for other spaces. Please reference our installation instructions for further details or contact sales@duratousa.com

*A 50'x50' install requires 10mm expansion space along walls in uncontrolled environments (such as no HVAC).

* Do not install below -19°F or above +176°F.

* Use a floor mat for office chairs.

SIZE/PACKAGING

PlankSize : 8.97"x70.86"

Planks/Carton : 4 Sq. Ft./Carton : 17.67

Cartons/Pallet : 52 Sq. Ft./Pallet : 918.84

Sq. Ft./Container : 16,539.12

FEATURES



AUTHENTEX™ FINISH
High-definition imagery plus and Embossed in Register creates an authentic wood look and texture.



CLIMATEGUARD™ RESISTANCE
Resists extreme temperatures, allowing product to be used in 3-season spaces.



LARGE AND LUXURIOUS
Ultra-long and extra-wide planks provide an upscale look, and are 89% larger than standard 7"x48" planks.



QUANTUM X™ TECHNOLOGY
Industry-leading resistance to scratches, stains and dents, strengthened by diamonds.



HEAVY COMMERCIAL USE
Durable enough to withstand heavy, everyday, foot traffic.

TEST DATA

ASTM E492-09 Impact Sound Conduction &	6", no drop ceiling: STC 52 / IIC 53 / HIIC 55
ASTM E90-09 Airborne Sound Conduction	Open web truss on OSB with gypsum and a drop: STC 61 / IIC 55 / HIIC 62

* Sound test scores are relative to varying conditions. For accurate results, contact Durato for on-site testing and/or specific buildouts.

ASTM D2394 Slip Resistance DCOF (Sliding)	Dry: 0.64 Wet: 0.51
---	------------------------

ASTM D1037 Dynamic Load Limit	2,200 psi
---	-----------

ASTM F970-22 Static Load Limit	Passes, 0.25mm indent, 250 psi
--	--------------------------------

ASTM F1914-18 Residual Indentation	Meets or Exceeds, average 0.03mm
--	----------------------------------

ASTM F2199-20 Dimensional Stability	Meets or Exceeds
---	------------------

ASTM E648 Critical Radiant Flux	Meets or Exceeds, Class 1 (>1.10)
---	-----------------------------------

ASTM F1514-19 Resistance to Heat and Cold	Meets or Exceeds, average ΔE* 0.27
---	------------------------------------

ASTM F1515-21 Resistance to Light	Meets or Exceeds, average ΔE* 0.64
---	------------------------------------

ASTM F925-13 Resistance to Chemicals	No change, Not affected
--	-------------------------

ASTM C518 Thermal Resistance	R Value -0.6
--	--------------

WARRANTY



LIMITED RESIDENTIAL WEAR WARRANTY LIMITED STRUCTURAL WARRANTY LIMITED WATERPROOF WARRANTY LIMITED COMMERCIAL WEAR WARRANTY LTD ENCLOSED PATIO & CABIN WARRANTY

