

- Proper maintenance will help preserve the appearance and long-term performance of your Durato SPC flooring. By following the recommendations below, you can keep your floor looking its best for years to come.
- After installation, perform an initial cleaning to remove any dust, dirt, or debris that may have accumulated during installation.
- Place walk-off mats at entrances to reduce dirt and moisture tracked onto the floor.
- Failure to follow recommended cleaning practices may affect product performance or warranty coverage.

DAILY CARE

- Sweep, dust mop, or vacuum regularly to remove dirt and debris.
- Clean spills immediately to prevent residue buildup.
- Use entry mats at exterior doors to help reduce dirt and moisture tracked onto the floor.

ROUTINE CLEANING

For regular maintenance cleaning:

- Use a damp microfiber mop with warm water and a small amount of mild pH-neutral floor cleaner or gentle dish soap.
- Rinse with clean water if residue remains.
- Change mop water frequently to prevent spreading dirt.
- Allow the floor to dry completely after cleaning.
- Circulating air with a fan may help speed drying.

Avoid excessive water or leaving standing water on the floor.

DEEP CLEANING

For heavier soil or residue buildup:

- Use warm water with a pH-neutral vinyl floor cleaner.
- Mop the floor and rinse thoroughly with clean water.
- Repeat if necessary until residue or haze is removed.

If buildup occurs over time, a mild degreasing cleaner followed by a thorough rinse with clean water may be used.

PROTECTING YOUR FLOOR

Durato SPC flooring is designed for durability, but proper care will help maintain the finish.

- Keep pet nails trimmed.
- Avoid walking on the floor with damaged high heels or exposed heel pins.
- Use protective felt pads under furniture legs.
- Use floor mats under rolling office chairs.
- Avoid dragging heavy objects across the floor.

FLOODING

In the event of significant flooding, contact a professional water remediation service.

COMMERCIAL MAINTENANCE

For commercial or high-traffic environments:

- Daily debris removal through sweeping or vacuuming
- Routine damp mopping as needed
- Periodic deep cleaning to remove buildup

Entry mat systems are strongly recommended.

SUNLIGHT & TEMPERATURE

Prolonged exposure to direct sunlight or extreme temperature changes may affect flooring performance.

- Use curtains or blinds during peak sunlight hours.
- Maintain a consistent indoor climate when possible.
- Avoid extreme temperature fluctuations.

WATER EXPOSURE

SPC flooring is water resistant; however, excessive moisture should not remain on the surface for extended periods.

If excessive water is present:

- Remove water as quickly as possible.
- Dry the area with towels, a mop, or wet vacuum.
- Use fans or dehumidifiers to return humidity levels to normal.

ACCEPTABLE CLEANING METHODS

- Damp mopping
- Microfiber mop cleaning
- Vacuuming using a hard floor setting
- Cleaning products designed for vinyl or resilient flooring

Avoid cleaners that contain:

- Ammonia
- Abrasive powders
- Harsh solvents
- Oil-based soaps
- Wax or polish

These products may damage the finish or leave residue on the floor.

STAIN REMOVAL

For difficult stains such as marker, paint, or adhesive residue:

1. Apply a small amount of isopropyl alcohol or vinyl floor cleaner to a soft cloth.
2. Gently wipe the stain until removed.
3. Rinse the area thoroughly with clean water.

Always test cleaning solutions in an inconspicuous area first.